

# Desert & River



Desert & River feature a 1mm woven vinyl surface layer fusion bonded to a 3mm vulcanized composition rubber base layer. The resulting surface provides safety, ergonomic, and acoustic benefits and a visual with both pattern and texture.

## Markets

- Corporate
- Hospitality
- Retail

## Applications

- Common Areas
- Retail
- Offices
- Public Spaces
- Living Spaces
- Cardio

## Benefits

- Durable
- Stain resistant
- Ergonomic
- Sustainable

# Product Information

### Nominal Dimensions:

Available as a standard in rolls. Talk to your local agent to determine availability, pricing, minimums, and lead times.



Rolls:  
4mm (1mm + 3mm) x 72" (1.83m) wide

[View Colors](#)

# Technical Details

Performance Criteria	Test Standard	Typical Results
Recovery After Static Load	ASTM F970	0.005"
Coefficient of Friction	ASTM D2047	>0.8
Flammability - Critical Radiant Flux	ASTM E648	Class I
Flammability - Pill Test	ASTM D2859	Pass
Abrasion Resistance	ASTM D3389	Pass
Dynamic Rolling Load	ASTM F2753	No change, No damage (@10,000 cycles)
Resistance to Light	ASTM F1515	Pass
Resistance to Heat	ASTM F1514	Pass
Impact Insulation Class (IIC)*	ASTM E492	52
Delta IIC*	ASTM E2179	22
Sound Transmission Class (STC)*	ASTM E90	55

\* Tested on a 6" concrete slab with no ceiling.

THE NRG FACTOR

NRG

=

>>>

6.82%

Force Reduction

Absorption of impact energy

>>>

71.82%

Energy Restitution

Useful return of impact energy

Safety

Ergonomics

Acoustics

ecosurfaces.com • 833-888-1760

BUILT ON

itsTRU

TECHNOLOGY

eco

surfaces