

Ecore 2020 Product Performance Summary

April 2020

Conducted on a 6" Slab - No Ceiling

Product	IIC	STC	Δ IIC	NRC	FIS	Heavy Weight Impact Sound Level (dBA)			Deltec Test	
						16lb Shot (39 3/8" drop height)	35lb Kettleball (18" drop height)	100lb Plate Weight (18" drop height)	Force Reduction (%)	Energy Restitution (%)
Vinyl Rx	52	56	23	0.15	77	91	—	—	11.5	72.0
Aurora Rx	52	53	24	—	77	—	—	—	11.2	67.4
Origins	46	53	19	—	81	—	—	—	2.4	75.5
ECOsurfaces Classic	48	51	19	0.05	—	—	—	—	2.4	75.5
ECOnights	51	50	22	0.10	—	87	93	—	10.97	67.7
ECOfit	54	51	24	0.10	—	89	94	—	14.5	66.7
ECOfit Plus	58	51	27	0.20	—	81	89	—	35.5	51.9
ECOmax 1"	56	52	26	0.20	—	68	73	88	46.3	52.1
ECOmax 2.5"	58	51	26	0.20	—	—	—	—	—	—
ECOsplash	59	49	29	0.25	—	53	58	62	67.7	46.1
FITturf	—	—	—	—	—	—	—	—	36.9	46.1
FITturf Plus	74	51	36	0.25	—	—	—	—	53.4	40.2

All Testing was conducted over a 6" slab with no ceiling.

Glossary:

IIC: Impact Insulation Class (Structure-borne Sound, ASTM E492)

STC: Sound Transmission Class (Airborne Sound, ASTM E90)

Delta IIC: Effectiveness of Floor Coverings in Reducing IIC (Structure-borne Sound, ASTM E2179)

NRC: Noise Reduction Coefficient (Airborne Sound Absorption Within a Room, ASTM C423)

FIS: Floor Impact Sound (Impact Sound in Room with Impact, ASTM E3133)

Contact your Ecore Commercial sales representative for more information and additional testing.

EcoreCommercial.com

877.258.0843